



# SHREE MARUTI NANDAN TUBES PVT. LTD.

Steel Pipes for Water, Gas  
and Sewerage Purpose  
Conforming to IS :3589 /EN-10224  
(Grade ERW 330 and 410)

N.B. Size MM	Outside Diameter MM	Wall Thickness MM	Weight (Plain End)	
			Kg / M	M/T
150	168.3	3.20	13.00	77
		4.50	18.20	55
		6.30	25.20	40
		7.10	28.20	35
200	219.1	3.60	19.10	52
		4.50	23.80	42
		5.20	27.40	36
		6.30	33.10	30
		7.10	37.10	27
		8.00	41.60	24
		8.40	43.60	23
250	273	3.60	23.90	42
		4.00	26.50	38
		4.30	28.50	35
		5.00	33.00	30
		5.60	36.90	27
		6.30	41.40	24
		7.10	46.60	21
		8.00	52.30	19
		8.40	54.80	18
		9.50	61.70	16
300	323.9	5.00	39.30	25
		5.60	44.00	23
		6.40	50.10	20
		7.10	55.50	18
		8.40	65.40	15
		9.50	73.70	14


A-21, 2nd Floor, Amrapali Complex,  
S.P. Ring Road, Bopal,  
Ahmedabad - 380 058. (Gujarat)  
079-65237660, 02717-237660, 235473  
E-mail : contact@shreemarutitubes.com

Steel Tubes for Water Wells  
(Casing Pipes)  
Conforming to IS : 4270  
(Grade FE 410)

N.B. Size MM	Outside Diameter MM	Wall Thickness MM	Weight (Plain End)	
			Kg / M	M/T
100	114.3	5.4	14.50	69
		7.1	23.50	43
125	141.3	5.4	18.10	55
		7.1	23.50	43
150	168.3	5.4	21.60	46
		7.1	28.20	35
175	193.7	6.4	29.60	34
		8.0	36.60	27
200	219.1	6.4	33.60	30
		8.0	41.60	24
225	244.5	7.1	41.60	24
		9.0	52.30	19
250	273.1	8.0	52.30	19
		10.0	64.90	15
300	323.9	8.0	62.30	16
		10.0	77.40	13

### TOLERANCES IS : 3589

A	Outside Diameter	$\pm 0.75 \%$
B	Thickness	$\pm 10 \%$
C	Weight	$\pm 7.5 \%$



MARK  
HISSAR